DMC 550S PROFILE





PANEL DETAILS

AVAILABLE WIDTHS

12", 15", 17", and 19"

STANDARD PANEL WIDTHS

15", 19"


*Drexel Metals design pressures, wind uplifts and test reports are for specific deck attachments, material gauges, clip spacing and panel widths. A complete specification and listing is available online at www.drexelmetals.com

SUBSTRATES AVAILABLE

- · Painted Galvalume 24ga and 26ga
- Drexlume[™] 24ga and 26ga
- · Aluminum .032"

IDEAL APPLICATION COMMERCIAL & RESIDENTIAL

A superior integral seam design and quick installation – that's the hallmark of the DMC 550S panel. This expertly crafted interlocking roof system provides a powerfully protective weathertight seam. The finished results deliver a substantial measure of quality and style that's certain to stand the test of time.



DMC 550S PROFILE



PROFILE




Single lock panel

PANEL RIB OPTIONS









Clip Relief









Small Pencil

Large Pencil

Large V

PRODUCT INFORMATION

FINISHES

Available in a wide variety of coatings and colors. See the Drexel Metals color charts for standard colors and paint specifications.

PANEL RIB

Factory made or field rolled to exact lengths options

- · Flat Panel
- · Clip Relief
- Striations
- · Bead
- · Small and Large V
- · Small and Large Pencil

INSTALLATION

Can be installed over plywood decking or insulated metal decking with approved underlayments. Please see Drexel Metals installation details for complete information.

SLOPE

Minimum slope 3:12

TESTING

- · UL 580 Wind Uplift (Class 90)
- · UL 2218 Class 4 Hail Impact
- · UL 263 Fire Certification
- UL 790 Class A Fire Rating
- · UL Environmental SRI Third-Party Verified
- · ASTM E-1646 Water Penetration
- · ASTM E-1680 Air Leakage

Testing in accordance with



WARRANTY

35 YEAR WARRANTY - GALVALUME AND ALUMINUM SUBSTRATES35 year non pro-rated PVDF Paint Warranty

High-performance painted metal roofing product, carefully tensioned leveled for superior flatness.

25 YEAR WARRANTY - DREXLUME SUBSTRATE

Mill finished Galvalume® with a two-sided, clear acrylic finish.

SHERWIN-WILLIAMS. Coil Coatings

CORPORATE HEADQUARTERS: 1234 GARDINER LANE, LOUISVILLE, KY 40213 | 888-321-9630 TOLL-FREE | 502-690-6174 FAX | DREXELMETALS.COM

©2023 Drexel Metals, Inc. All rights reserved. Galvalume® is a registered trademark of BEIC International, Inc. Sherwin-Williams® Coil Coatings is trademark of The Sherwin-Williams Company. Drexlume™ is a trademark of Drexel Metals, Inc. Colors shown represent the actual color as closely as possible. To ensure exact color for final approval, a metal color chip is available. Warranty statements mentioned are outlines; complete Limited Warranty information is available on request. No other warranty expressed or implied is applicable. Please call or visit drexelmetals.com or residentialmetalroof.com for more details.