


FACADE BR - Z-GIRT HEAD DETAIL - TIE-IN VERTICAL APPLICATION




THIS DETAIL DRAWING IS APPLICABLE TO ALL FACADE BR SERIES WALL PANEL PROFILES



KEYNOTES:

- TRIM FASTENERS ARE SELF-DRILL PANCAKE HEAD AND MUST BE BE INSTALLED IN A STAGGERED PATTERN
- · FASTENERS MUST PENETRATE STEEL SUBSTRATE BY 5/8" MINIMUM THREAD LENGTH



FLASHINGS

DISCLAIMER: DETAIL SHOWN FOR ILLUSTRATION PURPOSES ONLY, ACTUAL PROJECT DETAIL MAY VARY

JOB SPECIFIC FLASHING 18GA SUPPORT PLATE * (FASTENED @ EA. Z-GIRT) J- CHANNEL #10 - 16 x 1" DP3 PHD (12"o.c.) FACADE BR PANEL Z-GIRT

SCALE: 3" = 1'-0"

0 1 2 3 4 5 6 ir

EFFECTIVE DATE: 01-01-2023 SUBJECT TO CHANGE WITHOUT NOTICE ★ <u>NOTE:</u> MAY OM

MAY OMIT SUPPORT PLATE IF ATTACHING FLASHING TO STRUCTURAL MEMBER.