


FACADE BR - Z-GIRT

WALL TO SOFFIT DETAIL

VERTICAL APPLICATION




THIS DETAIL DRAWING IS APPLICABLE TO ALL FACADE BR SERIES WALL PANEL PROFILES



KEYNOTES:

- TRIM FASTENERS ARE SELF-DRILL PANCAKE HEAD AND MUST BE BE INSTALLED IN A STAGGERED PATTERN
- FASTENERS MUST PENETRATE STEEL SUBSTRATE BY 5/8" MINIMUM THREAD LENGTH



FLASHINGS

DISCLAIMER: DETAIL SHOWN FOR ILLUSTRATION PURPOSES ONLY, ACTUAL PROJECT DETAIL MAY VARY

SOFFIT J- CHANNEL DREXEL APPROVED TUBE SEALANT J- CHANNEL 1/8" x 3/16" POP RIVET (12" o.c.) #10 - 16 x 1" DP3 PHD (12"o.c.) FACADE BR PANEL 18GA SUPPORT PLATE * (FASTENED @ EA. Z-GIRT) FACADE BR PANEL

SCALE: 3" = 1'-0"

0 1 2 3 4 5 6 in

EFFECTIVE DATE: 01-01-2023

SUBJECT TO CHANGE WITHOUT NOTICE

★ NOTE:
MAY OMIT SUPPORT PLATE IF ATTACHING
FLASHING TO STRUCTURAL MEMBER.