


## FACADE HL - Z-GIRT

# WALL TO SOFFIT DETAIL

**VERTICAL APPLICATION** 




### THIS DETAIL DRAWING IS APPLICABLE TO ALL FACADE HL SERIES WALL PANEL PROFILES



### KEYNOTES:

- TRIM FASTENERS ARE SELF-DRILL PANCAKE HEAD AND MUST BE BE INSTALLED IN A STAGGERED PATTERN
- FASTENERS MUST PENETRATE STEEL SUBSTRATE BY 5/8" MINIMUM
  THREAD LENGTH



FLASHINGS

DISCLAIMER: DETAIL SHOWN FOR ILLUSTRATION PURPOSES ONLY, ACTUAL PROJECT DETAIL MAY VARY

# SOFFIT J- CHANNEL DREXEL APPROVED TUBE SEALANT J- CHANNEL 1/8" x 3/16" POP RIVET (12" o.c.) #10 - 16 x 1" DP3 PHD (12"o.c.) Z-GIRT FACADE HL PANEL 18GA SUPPORT PLATE \* (FASTENED @ EA. Z-GIRT)



★ NOTE:
MAY OMIT SUPPORT PLATE IF ATTACHING
FLASHING TO STRUCTURAL MEMBER.