


DEFEND-R CI NAIL BASE

POLYISOCYANURATE INSULATION BONDED TO OSB OR PLYWOOD FOR EXTERIOR WALL APPLICATIONS IN TYPE V CONSTRUCTION



Defend-R CI Nail Base is an energy efficient rigid insulation panel composed of a closed cell polyisocyanurate foam core bonded to a premium performance coated glass facer on one side and 7/16" or 5/8" OSB or plywood on the other. It is designed for use in Type V commercial and residential wall applications to provide both continuous insulation and an attachment substrate.

APPLICATIONS

- Provides continuous insulation (ci) for standard wood frame, FRT wood frame, steel stud, CMU and concrete exterior wall construction
- Suitable substrate for numerous claddings/finishes including metal, fiber cement siding, masonry, composite cladding systems, wood clapboards, wood shingles and vinyl siding
- Suitable for new construction and retrofit on commercial and residential exterior walls

PANEL CHARACTERISTICS

- Manufactured with NexGen Chemistry: Zero Ozone Depleting Potential (ODP); Contains no CFCs, HCFCs or HFCs; Virtually zero Global Warming Potential (GWP). Use of Drexel Metals products help reduce the carbon footprint of buildings.
- Polyiso offers increased R-value per inch vs mineral fiber, XPS or EPS options

- A superior combination of high insulating properties and nailable surface
- Provides improved dimensional stability and fire performance
- ASTM C 1289 Type V made with Type II Class 2 foam
- Available in 4' x 8' (1220mm x 2440mm) panels in thicknesses of 1.5" (38mm) - 4.7" (119mm)
- Available with 7/16" or 5/8" OSB
- Available with 5/8" or 3/4" Plywood

DEFEND-R CI NAIL BASE THERMAL VALUES WITH 5/8" PLYWOOD

Long Term Thermal Resistance Values are based on ASTM C 1289

Thickness (inches)	(mm)	LTTR R-Value
1.60	41	6.8
2.10	53	9.8
2.60	66	12.9
3.10	79	16.1
3.60	91	19.3
4.10	104	22.5
4.60	117	25.8

DEFEND-R CI NAIL BASE THERMAL VALUES WITH 7/16" OSB

Long Term Thermal Resistance Values are based on ASTM C 1289

Thickness (inches)	(mm)	LTTR R-Value
1.50	38	6.6
2.00	51	9.6
2.50	64	12.7
3.00	76	15.9
3.50	89	19.1
4.00	102	22.3
4.50	114	25.6

POTENTIAL LEED® CREDITS FOR POLYISO USE

Energy and Atmosphere

- Optimize Energy Performance

Materials and Resources

- Building Life-Cycle Impact Reduction
- Environment Product Declaration
- Material Reuse

DEFEND-R CI NAIL BASE

- Recycled Content
- Construction and Demolition Waste Management

Indoor Environmental Quality

- Thermal Comfort

STRUCTURAL

Defend-R CI Nail Base, up to 2.7" of total thickness, can be used as structural insulating sheathing when applied to wood studs. Please contact Drexel Metals for shear values, wind loads and attachment requirements.

FASTENING

Several factors are involved in the proper fastening of Defend-R CI Nail Base. These include overall thickness of the panel, the weight of the specified cladding and the type of support provided at the base of the wall assembly. Please contact Drexel Metals for assistance with fastening rate and fastener type.

POST-INSTALLATION EXPOSURE

Defend-R CI Nail Base is not intended to be left exposed for extended periods of time. During the time between the installation of the Defend-R CI Nail Base and the application of the exterior cladding it is recommended that the WRB be installed as soon as possible. If the WRB is not being installed right away it is recommended that the Defend-R CI Nail Base be protected from excess moisture and UV. All unfaced foam exposed directly to daylight can be taped with a compatible waterproof tape and the edges of the boards can be buttered with a sealant that is compatible with the WRB.

TYPICAL PHYSICAL PROPERTY DATA

Polyiso Foam Core Only

Physical Property	Test Method	Value
Compressive Strength	ASTM D 1621	20 psi* (138kPa, Grade 2)
Dimensional Stability	ASTM D 2126	2% linear change (7 days)
Moisture Vapor Transmission	ASTM E 96	<1 perm (57.5ng/(Pa·s·m ²))
Water Absorption	ASTM C 209	< 0.1% volume
Service Temperature		-100°F to 250°F (-73°C to 122°)
Resistance to Mold	ASTM D 3273	Passed (10)
Flame Spread Index	ASTM E 84	<75
Smoke Developed	ASTM E 84	<450

*Also available in 25 psi, Grade 3

CODES AND COMPLIANCES

- Designed for use in continuous insulation to assist in meeting the most current ASHRAE 90.1, IECC, IBC and IRC standards
- Incorporates APA-TECO Rated Exposure 1 OSB or Plywood
- ASTM C 1289
- IBC Chapter 26 and IRC section R316

JOB-SITE STORAGE

Construction practice dictates that all insulations should be protected from moisture and direct sunlight during job-site storage. Pallets of Defend-R CI Nail Base are double packaged in a UV resistant polyethylene bag. This moisture resistant package is designed for protection from the elements during flatbed shipment from our factories to the job-site. Outdoor storage for extended periods of time requires waterproof tarpaulins and elevated storage above ground level a minimum of 2". Additionally, we recommend slitting the bundle packaging vertically down the center of the two short sides to prevent moisture accumulation within the package.

WARNINGS AND LIMITATIONS

Insulation must be protected from open flame. Drexel Metals will not be responsible for specific building design by others, for deficiencies in construction or workmanship, for dangerous conditions on the job site or for improper storage and handling. Technical specifications shown in this literature are intended to be used as general guidelines only and are subject to change without notice. Call Drexel Metals for more specific details.

Note: Defend-R CI Nail Base is not intended for use below grade.

